



Model	MA15-A
Dimension	
Max. Working Height	17m
Max. Platform Height	15m
Max. Outreach	9.12m
Max. Up and Over Clearance	7.2m
A Length (stowed)	6.99m
B Width (stowed)	1.77m
C Height (stowed)	2.17m
D Wheelbase	2m
Ground Clearance	0.21m
Platform Size	1.5×0.76×1.1m
Performance	
Lift Capacity	230kg
Turntable Rotation	360°non-continuous
Platform Rotation	0/180°
Drive Speed (Stowed)	5km/h
Drive Speed (Raised)	1km/h
Gradeability	30%
Turning Radius (Inside)	1.1m
Turning Radius (Outside)	3.5m
Turntable Tailswing	0
Max. Tilt Angle(front to back/side to side)	5°/3°
Drive wheels number x Steering wheels number	2×2
Tire Specification/ Type	240-55D17.5(foam filled tire)
Power	
Battery Specifications	DC48/320Ah
Voltage	DC12V
Hydraulic Tank Capacity	35L
Weight	
Total Weight	6800kg



# MA15-A

## SELF-PROPELLED ARTICULATED BOOM

# HELI

### Product Highlights

- ★Electric drive, green and environmentally friendly
- ★Zero emissions, meeting the strict requirements of indoor and outdoor emissions on construction sites

### Compact Structure

- ★The entire series adopts compact design, while also considering high maintenance, and has stronger ability to operate in narrow and complex working conditions.

### Excellent Performance

- ★Equipped with a maximum working angle of 3 degrees as standard, the entire series have stronger adaptability to the working range and site.
- ★230kg load capacity, adaptable to multiple scenarios and working conditions

### Low Maintenance Costs

- ★Compared to diesel power, battery maintenance costs are lower, reducing overall operating costs.

### Electric Drive

- ★Low cost, low noise, low maintenance, green environmental friendly and energy conservation



### Standard Features

Hydraulic leveling platform	Mechanical release of driving brake	Horn and buzzer safety warnings
Automotive grade full tube sheath protection	Platform rotation	Maximum tilt angle of 3°
Tilt alarm	Over load Sensor	Flash light
Emergency stop system	Emergency lowering system	Diagnosis system

### Options Features

AC wiring to platform	Manual Box
Non-marking solid tires	T-BOX (GPS)