

HELI



OPL10-S

	Character			
1.01	Manufacturer			HEU
1.02	Model			OPL10-S
1.03	Drive mode			Electric (battery)
1.04	Driving mode			Stand-on
1.05	Load capacity	Q	kg	1000
1.06	Load center distance	C	mm	600
1.07	Track	Y	mm	1300
	Tyre			
2.01	Tyre type		1	Polyurethane
2.02	Wheels number, Front/rear(X=driven wheels)			1x/2
2.03	Track Width,rear	b11	mm	700
2.04	Wheel size, front		mm	φ250×80
2.05	Wheel size, rear		mm	φ128×73
	Dimension		N	
3.01	Height, mast lowered	h1	mm	1300
3.02	Lift height of platform	h3	mm	1200
3.03	Height, mast extended	h4	mm	2360
3.04	Height, fork lift	h15	mm	800
3.05	Height, fork lowered	h13	mm	70
3.06	Overall length	11	mm	2790
3.07	Length to shank of forks	12	mm	1720
3.08	Overall width	b1	mm	812
3.09	Fork size	s/e/l	mm	35×100×1070
3.10	Width across forks	b5	mm	200-750
3.11	Underground clearance at center of wheel base	m2	mm	35
3.12	Aisle width with pallet 1000x1200 (1200 refers to the pallet width across the fork)	Ast	mm	3157
3.13	Aisle width with pallet 800x1200 (800 refers to the pallet width along the fork)	Ast	mm	3178
3.14	Turning radius	Wa	mm	1535
	Performance			
4.01	Travelling speed,laden/unladen		km/h	7.7/7.8
4.02	Lifting speed, laden/unladen		m/s	0.1/0.15
4.03	Lowering speed,laden/unladen		m/s	0.07/0.08
4.04	Gradeability,laden/unladen		96	8/15
	Electrical configuration			
5.01	Drive moter power		kw	1.5
5.02	Lifting moter power		kw	2.2
5.04	Battery capacity		V/Ah	24/450
5.05	Battery dimensions I/w/h		mm	654x305x705
	Controller			CURTIS
5.07	Brake			Electromagnetic brake
	Weight		4 4	
6.01	Total weight(with battery)		kg	1650
6.02	Axle load, front/rear axle, laden		kg	944/706
6.03	Axle load, front/rear axle, unladen		kg	500/2150







789 Marshall Road, Malaga WA 6090 (08) 9248 8660 www.alliedforklifts.com.au